

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 30-10-2015 Revision date: 30-10-2015 Supersedes: 30-10-2015 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Eurol Lube PL-S
Product code : S009100
Product group : Trade product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : industrial use, professional use, consumer use

Use of the substance/mixture : Lubricant

Function or use category : Lubricants and additives

# 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Eurol bv. Energiestraat 12 P.O. Box P.O. Box 135

7442 DA Nijverdal - The Netherlands

T +31 548 615165

r.hilgers@eurol.com - www.eurol.com

### 1.4. Emergency telephone number

Emergency number : +31 548 615165

(Monday to Friday: 8:00 - 17:00)

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]Mixtures/Substances: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Not classified

# Adverse physicochemical, human health and environmental effects

No additional information available

# 2.2. Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

Child-resistant fastening : Not applicable Tactile warning : Not applicable

2.3. Other hazards

Other hazards not contributing to the classification : This product floats on water and may affect the oxygen-balance in the water. The base oil

contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT

classified as T/R45: May cause cancer" (Note L).".

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substances

Not applicable

# 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 918-481-9 (REACH-no) 01-2119457273-39	35 - 50	Asp. Tox. 1, H304
reaction mass of isomers of: mono-(2-tetradecyl)naphthalenes; di-(2-tetradecyl)naphthalenes; tri-(2-tetradecyl)naphthalenes	(CAS-No.) 132983-41-6 (EC-No.) 410-190-0 (EC Index-No.) 601-055-00-9 (REACH-no) 01-2119847896-17	10 - 25	Aquatic Chronic 4, H413
Naphthalenesulfonic acid, dinonyl-, calcium salt (2:1)	(CAS-No.) 57855-77-3 (EC-No.) 939-717-7 (REACH-no) 01-2119980985-16	1 - 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319

EN (English) 1/7

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H-statements: see section 16

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Seek medical attention if ill effect develops.

First-aid measures after inhalation : Take victim to fresh air, in a quiet place, in an half laying position and if necessary take

medical advice. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse. High-pressure injection under skin may cause serious

damage. Seek medical attention if ill effect or irritation develops.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate

flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain,

blinking, tears or redness persist.

First-aid measures after ingestion : Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep

head below the hips to prevent aspiration. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : At normal ambient temperatures this product will be unlikely to present an inhalation

hazard because of its low volatility. May be harmful by inhalation if exposure to vapour,

mists or fumes resulting from thermal decomposition products occurs.

Symptoms/effects after skin contact

: Unlikely to cause harm to the skin on brief or occasional contact but products occurs.

: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead

to local necrosis if the product is not surgically removed.

Symptoms/effects after eye contact : Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Symptoms/effects after ingestion : Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger

quantities may cause nausea and diarrhoea.

Symptoms/effects upon intravenous administration : Unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2), dry chemical powder, foam. Water fog.

Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metal oxides.

Explosion hazard : Not expected to be a fire/explosion hazard under normal conditions of use.

## 5.3. Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

Other information : Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and

public waters

# 6.1.1. For non-emergency personnel

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk

of splashing) then chemical resistant aprons and/or impervious chemical suits and boots

will be required. Use protective clothing.

Emergency procedures : Consider evacuation.

# 6.1.2. For emergency responders

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk

of splashing) then chemical resistant aprons and/or impervious chemical suits and boots

will be required.

Emergency procedures : No specific measures are necessary.

### 6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

30-10-2015 (Version: 1.0) EN (English) 2/7

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

# 6.3. Methods and material for containment and cleaning up

For containment : Large quantities: Contain large spillage with sand or earth

Methods for cleaning up : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust). Take up large spills with pump or vacuum and finish with dry chemical

absorbent

Other information : Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked

container for disposal in accordance with local regulations. On water, recover/skim from

surface and pour out in disposal container.

#### 6.4. Reference to other sections

For further information refer to section 13.

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous.

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and

promptly returned to a drum reconditioner or disposed of properly.

Precautions for safe handling : Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled.

Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or

smoke during use. Remove contaminated clothing and shoes.

Hygiene measures : Take all necessary measures to avoid accidental discharge of product

: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.

Storage conditions : Store in original container.

Incompatible products : Reacts vigorously with strong oxidizers and acids.

Maximum storage period : 5 year Storage temperature :  $\leq$  40 °C

Information on mixed storage : Keep away from : oxidizing materials. strong acids.

Storage area : Store at ambient temperature.

Special rules on packaging : Keep container tightly closed and dry.

#### 7.3. Specific end use(s)

No additional information available

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

#### 8.2. Exposure controls

# Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

### Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

#### Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

#### Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

# Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

30-10-2015 (Version: 1.0) EN (English) 3/7

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

# Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

#### Personal protective equipment symbol(s):





#### **Environmental exposure controls:**

See Heading 12. See Heading 6.

#### Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

#### Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

: > 240 °C

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state : liquid
Appearance : Oily. liquid.
Colour : Beige.
Odour : characteristic.
Odour threshold : no data available
pH : no data available

Relative evaporation rate (butylacetate=1) : < 0,1

Melting point: no data availableFreezing point: no data available

Boiling point : > 280 °C

Flash point : no data available

Decomposition temperature : no data available Flammability (solid, gas) : no data available Vapour Pressure 20°C : < 0,1 hPa

Relative vapour density at 20 °C : > 1 (air=1)

Relative density : no data available

Solubility : insoluble in water.

Log Pow : > 3
Viscosity, kinematic : 32 mm²/s

Viscosity, dynamic : no data available
Explosive properties : no data available
Oxidising properties : no data available
Explosive limits : 0,6 - 7 vol %

9.2. Other information

Auto-ignition temperature

VOC content : 0 %

Other properties : Gas/vapour heavier than air at 20'C.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions of use

# 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

# 10.4. Conditions to avoid

Moisture. Overheating.

30-10-2015 (Version: 1.0) EN (English) 4/7 30-10-2015 (Version: 1.0)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

# 10.5. Incompatible materials

Strong oxidizing agents. strong acids.

#### 10.6. Hazardous decomposition products

CO, CO2, POx, NOx, SOx, H2S. Metal oxides.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

: Not classified Acute toxicity (oral) Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
LD50 oral rat	> 5000 mg/kg (OECD 401 method)	
LD50 dermal rabbit	> 5000 mg/kg (OECD 402 method)	
LC50 inhalation rat (mg/l)	> 4,9 mg/l (OECD 403 method)	
Skin corrosion/irritation	: Not classified	

Serious eye damage/irritation : Not classified Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified : Not classified Reproductive toxicity STOT-single exposure Not classified STOT-repeated exposure : Not classified Aspiration hazard : Not classified

### **Eurol Lube PL-S**

Viscosity, kinematic 32 mm<sup>2</sup>/s

Other information Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely

route of exposure: ingestion, skin and eye.

# **SECTION 12: Ecological information**

	_			
12.1		<b>OYI</b>	CII	W
-		OA!		. y

Ecology - general : Ecotoxicological data have not been determined specifically for this product. Information

given is based on a knowledge of the components and the ecotoxicology of similar products

Ecology - water : This product floats on water and may affect the oxygen-balance in the water.

: Not classified Acute aquatic toxicity Chronic aquatic toxicity : Not classified

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
LC50 fish 1 > 1000 mg/l Oncorhynchus mykiss (Rainbow trout)		
EC50 Daphnia 1	> 1000 mg/l EC50 48h - Daphnia magna [mg/l]	
EC50 72h algae (1)	> 1000 mg/l Pseudokirchneriella subcapitata	
12.2. Persistence and degradability		

# **Eurol Lube PL-S**

Persistence and degradability Product is biodegradable.

# Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation 80 %

# 12.3. Bioaccumulative potential

# **Eurol Lube PL-S**

Log Pow	> 3

This product is not expected to bioaccumulate through food chains in the environment. Bioaccumulative potential

30-10-2015 (Version: 1.0) 5/7 EN (English)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil	
Eurol Lube PL-S	
9,	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Regional legislation (waste)

Waste disposal recommendations

: Disposal must be done according to official regulations.

: Dispose in a safe manner in accordance with local/national regulations. Do not discharge

into drains or the environment.

Additional information

: Hazardous waste.

Ecology - waste materials

: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.

European List of Waste (LoW) code

: 13 02 05\* - mineral-based non-chlorinated engine, gear and lubricating oils

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

IMDG	IATA	ADN	RID
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
	Not applicable  g name  Not applicable  class(es)  Not applicable  Not applicable  ards  Dangerous for the environment: No	Not applicable  g name  Not applicable  Dangerous for the environment: No	Not applicable  Not applicable

# 14.6. Special precautions for user

# **Overland transport**

no data available

# Transport by sea

no data available

# Air transport

no data available

### Inland waterway transport

no data available

### Rail transport

no data available

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

30-10-2015 (Version: 1.0) EN (English)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

VOC content : 0 %

Directive 2012/18/EU (SEVESO III)

### 15.1.2. National regulations

No additional information available

# 15.2. Chemical safety assessment

No additional information available

# **SECTION 16: Other information**

Full text of H- and EUH-statements:		
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H413	May cause long lasting harmful effects to aquatic life.	
EUH210	Safety data sheet available on request.	

# SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

30-10-2015 (Version: 1.0) EN (English) 7/7